

VIROQUA MUNI (Y51) 2 N UTC-6(-5DT) N43°34.78' W90°53.86'

1292 NOTAM FILE GRB

RWY 11-29: H4000X60 (ASPH) S-12 MIRL 0.7% up E

RWY 11: REIL. PAPI(P2L)—GA 3.0° TCH 35'.

RWY 29: REIL. PAPI(P2L)—GA 3.0° TCH 37'.

RWY 02-20: 2424X90 (TURF) 1.0% up SW

SERVICE: **FUEL** 100LL **LGT** MIRL Rwy 11-29 preset to low SS-SR; to incr instst and ACTVT REIL Rwy 11 and 29; PAPI Rwy 11 and 29—CTAF. Rwy end 29: PAPI unusbl byd 5 deg L of cntrl.

AIRPORT REMARKS: Unattended. 24 hr fuel avbl with credit card. Rwy 02-20 CLSD Nov 15 thru Apr 15. Rwy 02-20 has sharp 20' drop-off each end, and slopes downhill to the north approximately 1.5%. Rwy 02 mkd with yellow cones. Rwy 20 mkd with yellow cones.

AIRPORT MANAGER: 608-606-9563

WEATHER DATA SOURCES: AWOS-3P 118.975 (608) 637-2925.

COMMUNICATIONS: CTAF 122.9

® **MINNEAPOLIS CENTER APP/DEP CON** 128.6

CLEARANCE DELIVERY PHONE: For CD ctc Minneapolis ARTCC at 651-463-5588.

RADIO AIDS TO NAVIGATION: NOTAM FILE LSE.


LA CROSSE (T) DME 108.4 LSE Chan 21 N43°52.57' W91°15.36' 139° 23.7 NM to fld. 649.

DME unusable:

263°-278° byd 10 NM blo 3,000'

263°-278° byd 15 NM

329°-182°



CHICAGO

L-28G

IAP

VOLK FLD (VOK)(KVOK) ANG 1 N UTC-6(-5DT) N43°56.35' W90°15.19'

912 B TPA—See Remarks NOTAM FILE GRB Not insp.

RWY 09-27: H9000X150 (CONC-GRVD) PCN 44 R/A/W/T HIRL

RWY 09: MALSR. PAPI(P4L)—GA 3.0° TCH 53'.

RWY 27: ALSF1. PAPI(P4R)—GA 2.85° TCH 53'. Rgt ttc.

ARRESTING GEAR/SYSTEM

RWY 09 HOOK BAK12B(B)(1260')

HOOK BAK-12B(B)(1250') **RWY 27**

SERVICE: **OX** 1, 2 **LGT** When ATCT clsd ACTVT MALSR Rwy 09; ALSF-1 Rwy 27; PAPI Rwy 09 and 27; HIRL Rwy 09-27—CTAF or 239.5. SFL not available on PCL, available upon request with twr/base ops. Rwy 27 PAPI nstd, rgt side.

MILITARY—A-GEAR Nml BAK-12B(B) configuration: apch end down, dep end up; 20 min PN to reconnect apch end cable.

JASU (AM32A-60A) 6(A/M32A-86) **FUEL** A++ — Avbl ltd, exp possible gnd delay for req exceeding 10,000 gal. **FLUID** LPOX LOX **TRAN ALERT** Extremely ltd.

MILITARY REMARKS: Opr Mon-Fri 1400-2200Z except holidays, check NOTAM for current airfield hrs. See FLIP AP/1 Supplementary Arpt Remarks. **RSTD** Recommend use as emergency arpt only when rqr to land as soon as possible. PPR ctc Volk Fld DSN 871-1205, C608-427-1205. Issued PPR valid for ETA +/- 1 hr. Early/late arr/dep must be coordinated. After hr re-coordination or cancel will be passed to Base Ops standby personnel C608-343-0104. PPR must be received not later than 48 hours in advance of acft arrival or by 2200Z on Fri for the following Mon. Twy F 50' wide, aircrews must ctc airfield mgmt to utilize Twy E or Twy F. Twy G ltd to wingspan less than 44' and heli ttc. **CAUTION** Tnst crews be adzd ARFF CAT 9 with 9700 gallons. Nstd airfield paint mark near BAK-12 tape connectors and donuts for Rwy 09-27. The mark is a 4" wide yellow half-moon arc around the sheave, with one mark at each entrance. Twy E, F and G unltgd, unltg daytime VFR use, Follow-Me rqr for day IFR and ngt IFR/VFR use. Twy E and Twy F clnc violation—Aerospace gnd eqpt lctd w 58' fm twy cntrl. Nstd airfield paint mark on east apr to ID prkg spots. Nstd airfield paint mark on Twys E, F and west end of Twy A to id UAS equip placement. Use extreme caution for extensive unmanned aerial systems (UAS) ops in vicinity. When wind is from south/southwest expect possible low level wind shear 1 to 3 NM on final to Rwy 27. Due to tactical acft rqr, BAK-12 cable may be in position for Rwy 09-27 simultaneously. BASH Phase I All dates not designated as Phase II. Phase II in effect 1 Sep to 30 Nov and 1 Mar to 31 May. **TFC PAT** Left ttc Rwy 09. TPA—helicopter rectangular 1500(588). VFR pat ltd to 3 acft fr 0559-1400Z. **MISC** First 1600' Rwy 09 and first 1600' Rwy 27 grooved concrete, mid 5800' grooved asphalt. Standard USAF RSRs applied. Base Ops DSN 871-1205, C608-427-1205. ComSec unavbl, mnm ovngt classified storage avbl for tsnt aircrews. Lavatory svc unavbl.

AIRPORT MANAGER: 608-427-1205

CHICAGO

H-2K, L-28G

DIAP, AD

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

COMMUNICATIONS: CTAF 127.5 ATIS 134.35 257.85 PTD 372.2

® APP/DEP CON 135.25 244.875 (1400–2200Z† Mon–Fri exc holidays; other times ctc)

® CHICAGO CENTER APP/DEP CON 125.05 269.375

TOWER 127.5 239.25 (1400–2200Z† Mon–Fri; exc hol, clsd other times except validated overseas or ANG mission, check NOTAMS for current afld hrs.)

GND CON 121.9 275.8 SHEBOYGAN RANGE 260.4

HARDWOOD RANGE 34.2 297.75 358.8

CLEARANCE DELIVERY PHONE: When ATCT clsd, for CD ctc Chicago ARTCC at 630-906-8921.

AIRSPACE: CLASS D svc 1400–2200Z† Mon–Fri, exc hol, clsd other times exc validates overseas or ANG msn, ck NOTAM for current afld hr; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE GRB.

(L) TACAN Chan 41 VOK (110.4) N43°56.57' W90°15.54' at fld. 903/OE. TACAN unmonitored 1600–0800.

TACAN No NOTAM MP: 1400–1530Z† Mon

DME unusable:

130°–164° byd 25 NM

165°–175°

176°–260° byd 25 NM

280°–300° byd 30 NM

TAC AZM unusable:

165°–175°

185°–232° byd 25

ILS 108.5 I–VOK Rwy 27. Class IE. No NOTAM MP: Localizer–1930–2030Z† Mon; GS–2030–2130Z† Mon.

Unmonitored when twr clsd. LOC unusable byd 25° right of course.

COMM/NAV/WEATHER REMARKS: Limited Special Rules Area svc avbl, ctc Radar Approach Control at DSN 871–1779, C608–427–1779.

WALWORTH

BIG FOOT AIRFIELD (7V3) 3 W UTC–6(–5DT) N42°31.63' W88°39.08'

CHICAGO

948 TPA—1748(800) NOTAM FILE GRB

RWY 18–36: 2114X100 (TURF) LIRL(NSTD)

SERVICE: LGT ACTIVATE LIRL Rwy 18–36—123.75. Rwy 18–36 NSTD LIRL; Rwy 18 thld lgts are 45' south of rwy markers.

AIRPORT REMARKS: Unattended. Rwy not plowed winter months—open to ski equipped acft only. Rwy 18–36 mkd with yellow half barrels.

AIRPORT MANAGER: (262) 745-3299

COMMUNICATIONS: CTAF 122.9

CLEARANCE DELIVERY PHONE: For CD ctc Chicago ARTCC at 630-906-8921.

WASHINGTON ISLAND (2P2) 1 S UTC–6(–5DT) N45°23.30' W86°55.44'

GREEN BAY
IAP

653 B NOTAM FILE GRB

RWY 02–20: 2250X150 (TURF) LIRL 0.3% up S

RWY 02: Trees.

RWY 20: Trees.

RWY 14–32: 2232X150 (TURF) LIRL 0.7% up NW

RWY 14: Trees.

RWY 32: Tree.

SERVICE: LGT LIRL Rwy 02–20 opr SS–SR and preset to low intst; to incr intst and ACTVT LIRL Rwy 02–20 and 14–32—CTAF.

AIRPORT REMARKS: Unattended. Rwy 14–32 +12' rise in rwy elevation northwest 900'. Numerous flocks of waterfowl and deer on and invof arpt. Rws 14–32 and 02–20 plowed when snow is over 3 inches confirm conds 920–535–0979. Rwy 02 and 20 and Rwy 14 and 32 marked with yellow cones.

AIRPORT MANAGER: (920) 535-0546

WEATHER DATA SOURCES: AWOS–3PT 118.525 (920) 847–3024.

COMMUNICATIONS: CTAF 122.9

® MINNEAPOLIS CENTER APP/DEP CON 127.65

CLEARANCE DELIVERY PHONE: For CD ctc Minneapolis ARTCC at 651-463-5588.