

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D svc 1200-0300Z†; other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE IAH.

HUMBLE (H) (H) VORTACW 116.6 IAH Chan 113 N29°57.42' W95°20.74' 346° 24.0 NM to fld. 81/5E.

VORTAC monitored by ATCT

VOR portion unusable:

060°-070° byd 35 NM

175°-185° byd 20 NM blo 3,000'

Byd 30 NM blo 2,000'

DME unusable:

015°-090° byd 30 NM blo 2,000'

130°-320° byd 30 NM blo 2,000'

175°-185° byd 20 NM blo 3,000'

230°-250°

TACAN AZIMUTH unusable:

040°-055° blo 5,000'

150°-320° blo 4,500'

150°-320° byd 10 NM

ALIBI NDB (LOMW) 281 CX N30°25.92' W95°28.58' 141° 5.7 NM to fld. 371/5E. NOTAM FILE CXO.

ILS/DME 108.7 I-CXO Chan 24 Rwy 14. Class IA. LOM ALIBI NDB.

DAN JONES INTL (T51) 22 NW UTC-6(-5DT) N30°02.57' W95°40.03'

HOUSTON

166 B NOTAM FILE CXO

COPTER

RWY 17-35: H3440X50 (ASPH-TURF) LIRL(NSTD)

L-19D, 21A, GOAW

RWY 17: Thld dsplcd 255'. Trees.

RWY 35: Thld dsplcd 380'. P-line.

SERVICE: S4 **FUEL** 100LL **LGT** SS-SR, ACTIVATE LIRL Rwy 17-35—CTAF. For rotating bcn call 936-521-9887. Rwy 17-35 NSTD LIRL, NSTD colors, single thr lgt each rwy end. 2240 ft of rwy usbl for ngt opns. Rwy 17 thr relctd 300 ft for ngt opns: Rwy 35 thr relctd 900' ft for ngt ops.

AIRPORT REMARKS: Attended dawn to 0600Z†. Arpt CLOSED midnight to dawn. Deer on rwys. Cattle invof rwy. PPR for rotor wing acft. Rwy 17 thr bar 2 ft wide. Rwy 17-35 north end 2365 ft X 30 ft asph. Rwy 35 south 1000 ft of rwy turf, no mkg. Rwy 17 thr dsplcd 255 ft days only. Rwy 35 thr dsplcd 400 ft days only. Rwy 17-35 4 ft fence 53 ft east of cntrln. Left hand tfc 500' and 1000' MSL. North-South transitional acft west of fld. Ldg fee.

AIRPORT MANAGER: 936-521-9887

COMMUNICATIONS: CTAF/UNICOM 122.8

CLEARANCE DELIVERY PHONE: For CD ctc Houston Apch at 281-443-5844 to cnl IFR call 281-443-5888.

RADIO AIDS TO NAVIGATION: NOTAM FILE CXO.

NAVASOTA (VH) (H) VORW/DME 115.9 TNV Chan 106 N30°17.31' W96°03.49' 118° 25.1 NM to fld. 247/8E.

DME unusable:

010°-095° byd 28 NM blo 3,000'

096°-106° byd 18 NM blo 3,000'

VOR unusable:

025°-085° byd 40 NM

025°-095° byd 28 NM blo 3,000'

096°-114° byd 19 NM blo 2,000'

115°-124° blo 5,000'

125°-131° byd 30 NM blo 3,000'

142°-145° byd 26 NM blo 5,000'

146°-359° byd 18 NM blo 2,000'

215°-230° byd 40 NM

240°-255° byd 40 NM blo 2,100'

240°-255° byd 52 NM

256°-260° byd 40 NM

261°-271° byd 39 NM blo 5,000'

261°-271° byd 59 NM blo 7,000'

261°-271° byd 82 NM

272°-328° byd 40 NM

329°-339° byd 40 NM blo 5,000'

329°-339° byd 61 NM blo 6,000'

329°-339° byd 83 NM

356°-005° byd 40 NM