

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE FTW.

GROESBECK (L) DME 108.8 GNL Chan 25 N31°34.89' W96°32.95' 026° 4.0 NM to fld. 514.

DME unusable:

150°-205° byd 30 NM blo 2,500'

230°-310° byd 30 NM blo 2,400'

345°-035° byd 35 NM blo 2,500'

MIAMI-ROBERTS CO (3E0) 3 NE UTC-6(-5DT) N35°42.84' W100°36.19'**DALLAS-FT WORTH**

2720 NOTAM FILE FTW

L-15C

RWY 02-20: H4060X50 (ASPH) S-12.5 LIRL

RWY 02: Trees.

RWY 20: Thld dsplcd 390'. Hill. Rgt tfc.

SERVICE: LGT ACTVT LIRL Rwy 02-20—CTAF. Rwy 20, 3 red lgts outboard each side of rwy edge, 188 ft fm N end of rwy.

AIRPORT REMARKS: Unattended. Rwy has 25 ft drop off at S end.

AIRPORT MANAGER: 806-868-3721

COMMUNICATIONS: CTAF 122.9

CLEARANCE DELIVERY PHONE: For CD ctc Albuquerque ARTCC at 505-856-4861.

RADIO AIDS TO NAVIGATION: NOTAM FILE BGD.

BORGER (L) TACAN Chan 23 BGD (108.6) N35°48.42' W101°22.93' 087° 38.4 NM to fld. 3130/11E.

TACAN AZIMUTH unusable:

220°-320° byd 10 NM blo 12,000'

MID VALLEY INTL (See WESLACO on page 459)**MID-WAY RGNL** (See MIDLOTHIAN/WAXAHACHIE on page 394)**MIDLAND****MIDLAND AIRPARK** (MDD)(KMDD) 3 N UTC-6(-5DT) N32°02.19' W102°06.09'**ALBUQUERQUE**

2805 B NOTAM FILE MDD

H-66, L-6H

RWY 07-25: H5571X75 (ASPH-RFSC) S-18.5 MIRL 0.3% up W

IAP

RWY 07: PAPI(P2L)—GA 3.0° TCH 40'. Thld dsplcd 550'. Pole.

RWY 25: VASI(V4L)—GA 3.0° TCH 53'. Pole. Rgt tfc.

RWY 16-34: H3839X75 (ASPH) S-18.5 MIRL

RWY 16: PAPI(P2L)—GA 3.0° TCH 40'. Road.

RWY 34: PAPI(P2L)—GA 3.0° TCH 40'. Trees. Rgt tfc.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 07: TORA-5571 TODA-5571 ASDA-5571 LDA-5022

SERVICE: S4 FUEL 100LL, JET A OX 1, 3 LGT MIRL Rwy 07-25 and

16-34 preset low intst; to incr intst and ACTVT VASI Rwy 25; PAPI

Rwy 07, 16 and 34—CTAF.

AIRPORT REMARKS: Attended Mon-Fri 1200-0200Z†, Sat-Sun

1300-0200Z†. Birds invof arpt (seasonal). 100LL: for fuel aft hrs call

432-685-7000. Oprs on non-paved sfcs are prohibited without 24

hr PPR.

AIRPORT MANAGER: 432-560-2200

WEATHER DATA SOURCES: AWOS-3 118.125 (432) 687-4605.

COMMUNICATIONS: CTAF/UNICOM 122.7


® MIDLAND APP/DEP CON 124.6 (1200-0600Z†)

® FORT WORTH CENTER APP/DEP CON 133.1 (0600-1200Z†)

CLNC DEL 121.8

CLEARANCE DELIVERY PHONE: For CD when 121.8 is ots ctc Midland Apch at 432-563-2123. When Apch clsd ctc Fort Worth

ARTCC at 817-858-7584.



CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE MAF.

(VL) (H) VORTACW 112.6 MAF Chan 73 N32°00.56' W102°11.42' 059° 4.8 NM to fld. 2860/11E.

VOR unusable:

010°-020° byd 8 NM blo 8,000'

207°-262° byd 40 NM

263°-273° byd 53 NM

274°-322° byd 40 NM

343°-349° byd 40 NM

TACAN AZIMUTH unusable:

167°-169° byd 10 NM

200°-294° byd 14 NM

295°-305° byd 14 NM blo 12,000'

295°-305° byd 18 NM

306°-335° byd 14 NM

DME unusable:

167°-169° byd 10 NM

200°-294° byd 14 NM

295°-305° byd 14 NM blo 12,000'

295°-305° byd 18 NM

306°-335° byd 14 NM

MIDLAND INTL AIR AND SPACE PORT (MAF)(KMAF) 8 SW UTC-6(-5DT) N31°56.55'

SAN ANTONIO

W102°12.12'

H-6G, L-6H

2872 B ARFF Index—See Remarks NOTAM FILE MAF MON Airport

IAP, AD

RWY 16R-34L: H9501X150 (ASPH-GRVD) S-160, D-200, 2S-175, 2D-350, 2D/2D2-700

PCR 730 F/B/X/T HIRL

RWY 16R: PAPI(P4L)—GA 3.0° TCH 50'.

RWY 34L: REIL. PAPI(P4L)—GA 3.0° TCH 50'. Pole.

RWY 10-28: H8302X150 (ASPH-GRVD) S-160, D-200, 2S-175, 2D-350, 2D/2D2-700 PCR 660 F/B/X/T HIRL

RWY 10: MALS. PAPI(P4L)—GA 3.0° TCH 54'. RVR-T

RWY 28: MALS. PAPI(P4R)—GA 3.0° TCH 53'. RVR-R Thld dsplcd 691'.

RWY 04-22: H4605X75 (ASPH) S-30, D-60 PCN 19 F/B/X/T MIRL No Part 121/Part 380 Ops

RWY 04: Pole.

RWY 22: Road.

RWY 16L-34R: H4247X100 (ASPH) S-30, D-60 PCN 19 F/B/X/T MIRL 0.4% up N No Part 121/Part 380 Ops

RWY 16L: Fence.

RWY 34R: Road.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 04: TORA-4605 TODA-4605 ASDA-4605 LDA-4605

RWY 10: TORA-8302 TODA-8302 ASDA-8177 LDA-8177

RWY 16L: TORA-4247 TODA-4247 ASDA-4247 LDA-4247

RWY 16R: TORA-9501 TODA-9501 ASDA-9501 LDA-9501

RWY 22: TORA-4605 TODA-4605 ASDA-4605 LDA-4605

RWY 28: TORA-8302 TODA-8302 ASDA-8302 LDA-7610

RWY 34L: TORA-9501 TODA-9501 ASDA-9501 LDA-9501

RWY 34R: TORA-4247 TODA-4247 ASDA-4247 LDA-4247

SERVICE: S4 FUEL 100LL, JET A, A1 OX 2, 4 LGT ATC ctl. When ATCT clsd HIRL Rwy 10-28 and 16R-34L preset on low intst. When ATCT clsd ACTVT MALS. Rwy 10; MALS Rwy 28; MIRL Rwy 04-22 and 16L-34R—CTAF.

AIRPORT REMARKS: Attended continuously. Bird activity on and invof arpt. Rwy 04-22 and 16L-34R clsd to acft over 60,000 lbs. Rwy 10-28 E 692' CLOSED to acft over 60,000 lbs. Rwy 16R-34L 180° turn prohibited to acft 60,000 lbs and abv. Rwy 10-28 180° turn prohibited to acft 60,000 lbs or abv. Taxiways B and F north Rwy 10-28 clsd to acft over 60,000 lbs. Nmrs oil rigs invof arpt at or blw 200' AGL. Class I, ARFF Index C. For ARFF svc btn 0600-1200Z† dly ctc FSS at 800-992-7433. All runup pads are ltd usage to acft 60000 lbs or blw. Rwy 04-22 and 16L-35R are CLOSED to acft over 60,000 lbs. Oprs on non paved sfc are prohibited wo 24 hr PPR. Ldg fee. User Fee arpt.

AIRPORT MANAGER: 432-560-2200

WEATHER DATA SOURCES: ASOS (432) 201-2813 LLWAS.

COMMUNICATIONS: CTAF 118.7 ATIS 126.8 UNICOM 122.95

RCO 122.6 (SAN ANGELO RADIO)

® APP/DEP CON 124.6 (241°-136°) 121.1 (137°-240°) (1200-0600Z†)

® FORT WORTH CENTER APP/DEP CON 133.1 (0600-1200Z†)

TOWER 118.7 (1200-0600Z†) GND CON 121.9 CLNC DEL 118.05

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Fort Worth ARTCC at 817-858-7584.

AIRSPACE: CLASS C svc ctc APP CON svc (per TWR/NOTAM 1200-0600Z†); other times CLASS E.

CONTINUED ON NEXT PAGE