

KELLY FLD (SKF)(KSKF) CIV/MIL AF (ANG AFRC) 4 SW UTC-6(-5DT) N29°23.05' W98°34.87' **SAN ANTONIO**
 691 B NOTAM FILE SKF **H-7B, L-19C**
RWY 16-34: H11550X150 (CONC-GRVD) PCN 58 R/B/W/T HIRL **IAP, DIAP, AD**
RWY 16: ALSF1. PAPI(P4L)—GA 3.0° TCH 89'. RVR-TR
RWY 34: ALSF1. PAPI(P4R)—GA 3.0° TCH 93'. RVR-TR

ARRESTING GEAR/SYSTEM
RWY 16 BAK-14 BAK-12A(B) (1853'). BAK-14 BAK-12A(B) (1677') HOOK MB100 (60' OVRN). **RWY 34**
SERVICE: S4 **FUEL** 100LL, JET A+ **OX** 1, 2 **LGT** Rwy 34 PAPI (nstd), located on right (east) side of Rwy 34. Twy F: No
 twy end lgts. Bcn lgts OTS. **MILITARY— A-GEAR** BAK-12A(B) cables raised by BAK-14 device O/R to ctl twr. Potential for
 hook skip at BAK-12 cable sys due to irreg edges and uneven depths within 200' of arresting sys. **JASU** (A/M32A-86D,
 A/M32A-95 LASS) **FUEL** A++ , A+ , J8, (J8 1200-0600Z, call out fee \$50, 2 hr prior notice for defueling and reserve)
 Mil fuel unavbl Sat 0400-1200Z. (Mil) **FLUID** SP PRESAIR LHOX LOX LHNIT **OIL** O-133-148-156 SOAP - Avbl
 2000-0600Z Mon, 1230-0600Z Tue-Thu, 1230-2230Z Fri **TRAN ALERT** Opr 1130-0430Z Mon-Fri, 1330-0230Z
 Sat-Sun, clsd Federal hol; OT 2 hr PN rqr ctc AMOPS. 1 hr PN for all acft svc; ctc AMOPS DSN 945-6803,
 C210-925-6803 or PTD to avoid delays. Una to support tran acft lcl sorties.

NOISE: Quiet hrs 0500-1200Z dly departure and full-stop ldg only. Acft arr btn 0500-1200Z exp full stop ldg. No after
 burner tkof during these times without prior coord and apvl.

AIRPORT REMARKS: Aerodrome clsd dly fm 2300L-0700L. Only pre-apvd acft with 24-48 hrs notice are pmtd to arr/dep durg
 closure hrs. Ctc arpt mgmt for pre-apvl cdn at comm/DSN 210-925-6803/945-6803. Probability of hydroplaning at all
 speeds entire rwy. Acft with wingspan larger than 93' not authorized in Arm/DeArm Pads. Civ ramp lctd northeast of rwy.
 Twy G west of Twy H is for 149FW use. Ctc FBO 210-921-6100 for svc, JET A+ , 100LL full service ARINC 129.725,
 1200-0600Z, 2 hrs pn rqr outside nml hrs. Acft using Avgas self-serve: do not deviate fm tax lns to/fm avgas self-serve
 to ensure safe dstc fm otr opns. 100LL fuel is full service at FBO. Apn PSA Ramp clsd in both drctns at Twy B at apn
 entrance to Twy C to all acft unless under tow. User fee arpt. Customs/AG/IMG rqr 72 hrs PN ctc FBO 1200-0600Z. 2
 hr PN for defueling and reserve. For civilian operations, contact Port Operations 210-362-7875, PTD Airband 122.95.
 User fees applicable to civ acft. Lndg fee: landing fee for all acft excluding U.S. Mil and acft less than 12,500 lbs. Invoiced
 by PSA airport department, IAW JUA.

MILITARY REMARKS: Attended continuously. **RSTD** Tran acft exp delays and may be ltd to one apch to a full stop for home stn
 formal trng unit ops and tactical arr and dep trng 1500-0400Z, Mon-Fri. Warning: Large successive flocks of cattle
 egrets, 5 to 50 in nr have been observed flying blw 300' AGL across N end of rwy every morning at SR for up to 2 hrs,
 returning within 2 hrs of SS. BASH Phase II in eff 1 Mar-30 Nov. Req for PPR will be taken no earlier than 7 days prior
 to planned mission. At least 24 hr pn rqr for PPR, exc medevac, dv and other acft on a case by case basis apvd by DO.
 Ctc base ops DSN 945-6803, C210-924-6803. PPR good for +1/-1 hr PPR block time. Coord of PPR outside of block
 time by fone is rqr'd. **CAUTION** North end underrun/ovrn 147' paved, 853' unpaved. Rwy and majority of twy pavement
 shoulders exceed standard dimensions and are not marked with yellow chevron, deceptive surface markings to indicate
 unusable. Heavy rubber deposits obscuring rwy markings at TDZS. Inst hold line mrk faded on Twy F. First 960' x 150'
 Rwy 16, First 1022' x 150' Rwy 34 grooved conc. Rwy 16-34 mid rollout 9568' x 75' grooved conc. Mid rollout 37.5'
 inward fm rwy side stripe/edge mrkgs ungrooved. Friction inadequate due to rubber buildup at rwy TD zones. Conds
 worsen when RSC wet. **TFC PAT** Rectangular 1700 ft MSL, convl 2200 ft MSL, ftr type/overhead 2700 ft MSL. AETC acft
 exp reduced rwy separation day/VFR. Tran ftr acft must notify twr on initial ctc of reduced separation is not
 desired. **CSTMS/AG/IMG** rqr 72 hrs PN ctc FBO. User fee arpt: Cstms; plant quarantine and IMG svc avbl ctc Base Opns 2
 hrs PN. All psnl must clear IMG inbd. **MISC** USAF Tran Acft will use tran alert svc and park on mil ramp. Non-USAF Tran
 Acft may prk at mil ramp or FBO on civ ramp; for qns ctc afld mgmt opns C210-925-6803. Acft with Code 6 and abv
 ctc AMOPS phone patch/PTD with block time at least 1 hr before ldg. User fees applicable to civ acft. Official point of
 obsn does not allow a clear unobstructed view of rwy. WX technician view from North to SE is partially obstructed by trees,
 bldgs, and hangars. Technician relies on cooperative wx Watch with twr. High ints security lgts hinder ability to determine
 sky cond at ngt. AFRC PPR for use of AFRC ramp, DSN 945-4330, C210-925-4330. Rwy cond code (RWYCC) not rptd.
 Ltd classified mtrls storage: excess and ts mtrls must go to 433 AW/CP. TACAN ck point /altm sign on Twy F and B sited
 opposite drctn of TACAN. **ANG** Opr Tue-Sat 1345-2230Z. PPR for use of ANG ramp, DSN 945-5934, C210-925-5934.

AIRPORT MANAGER: 210-925-5879

COMMUNICATIONS: ATIS 120.45 273.5 (24 hrs) **PTD** 126.2 372.2 **PTD AIRBAND** 122.95

① **SAN ANTONIO APP CON** 118.05 125.1 127.1 289.2 307.0 353.5
KELLY TOWER 124.3 322.35
GND CON 121.8 289.4

① **SAN ANTONIO DEP CON** 125.7 290.225
AFRC COMD POST 138.6 252.1 (502 ABW DSN 471-9363 C210-221-9363) **PMSV METRO** 239.8 (Full svc 24 hr, unless
 afld clsd by AMOPS via NOTAM. Wx DSN 945-5709 C210-925-5709. Afld wx is monitored by AN/FMQ-19 ASOS.
 Remote briefing svc avbl 26 OWS, Barksdale AFB DSN 331-2651, C318-529-2651.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D.

RADIO AIDS TO NAVIGATION: NOTAM FILE SKF.

(L) TACAN Chan 57 KSY (112.0) N29°23.50' W98°34.86' at fld. 687/4E. TACAN unmonitored when ATCT clsd.

No NOTAM MP: 0600-1430Z± Wed

TACAN AZIMUTH unusable:

163°-188° byd 14 NM blo 2,700'

298°-318° byd 20 NM blo 4,600'

346°-356° byd 16 NM blo 3,400'

DME unusable:

163°-188° byd 14 NM blo 2,700'

298°-318° byd 20 NM blo 4,600'

346°-356° byd 16 NM blo 3,400'

ILS 110.1 I-SKF Rwy 16. Class IT. No NOTAM MP: 0600-1430Z± Mon and Tue.

ILS 110.7 I-OSQ Rwy 34. Class IT. No NOTAM MP: 0600-1430Z± Mon and Tue.

KESTREL AIRPARK (1T7) 23 N UTC-6(—5DT) N29°48.71' W98°25.56'

SAN ANTONIO

1261 NOTAM FILE SJT

L-19C

RWY 12-30: H3000X40 (ASPH) LIRL 1.4% up NW

RWY 12: Trees.

RWY 30: Road. Rgt ttc.

SERVICE: S4 FUEL 100LL OX 1

AIRPORT REMARKS: Attended continuously. Self serv fuel. For assistance call 830-522-1885. Deer on and invof rwy. Rwy 30 rises rapidly at north end. Rwy 12 end 49 ft higher than Rwy 30 end. TGL and low apchs prohibited for tran and coml acft. Tkofs rstrd btn 0400-1200Z±. Hel trng ops prohibited. Use extreme ctn for mil acft from Randolph AFB at or abv 3000 ft MSL Mon-Fri 1600-0600Z± and when twr hrs extd by NOTAM, ocnl Sat and Sun. Rwy 12 120 ft rising trm 0.4 mi NW of rwy end. Nstd aiming point markings at 500 ft, 2490 ft remaining. Rwy 12 calm wind rwy. Rwy 12-30 now marked as 13-31. Rwy 30 nstd aiming point mkgs at 300 ft.

AIRPORT MANAGER: 210-504-8992

COMMUNICATIONS: CTAF/UNICOM 122.975

CLEARANCE DELIVERY PHONE: For CD etc San Antonio Apch at 210-805-5516.

RADIO AIDS TO NAVIGATION: NOTAM FILE SAT.

SAN ANTONIO (VH) (H) VORTACW 116.8 SAT Chan 115 N29°38.64' W98°27.68' 002° 10.2 NM to fld. 1159/8E.

VOR unusable:

018°-022° byd 40 NM

028°-032° byd 40 NM

342°-347° byd 40 NM

355°-002° byd 40 NM blo 18,000'