

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D svc 1200-0300Z±; other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE ORL.

(VH) (H) VORTACW 112.2 ORL Chan 59 N28°32.56' W81°20.10' at fld. 102/OE.

TACAN AZIMUTH unusable:

066°-084°

246°-289° byd 17 NM blo 2,000'

246°-289° byd 28 NM blo 2,500'

VOR unusable:

075°-089° byd 40 NM blo 8,000'

075°-089° byd 53 NM

090°-100° byd 40 NM

235°-245° byd 40 NM

260°-296° byd 40 NM blo 2,000'

260°-296° byd 46 NM blo 5,000'

260°-296° byd 57 NM

300°-314° byd 40 NM blo 4,000'

300°-314° byd 55 NM blo 6,000'

300°-314° byd 66 NM

320°-330° byd 40 NM

340°-345° byd 40 NM

ILS 109.9 I-ORL Rwy 07. Class IB. Unmonitored when ATCT clsd. Autopilot cpd apch NA blw 320' MSL.

ILS/DME 109.35 I-EXO Chan 30(Y) Rwy 25. Unmonitored when ATCT clsd.

COMM/NAV/WEATHER REMARKS: ATC radar req when ORL ILS Rwy 07 and MCO ILS Rwy 17 and 18R simultaneous ops are conducted.

ORLANDO INTL (MCO)(KMCO) P (AF) 6 SE UTC-5(-4DT) N28°25.76' W81°18.54'

JACKSONVILLE

96 B LRA Class I, ARFF Index E NOTAM FILE MCO

H-8H, L-21D, 24F

RWY 18L-36R: H12005X200 (ASPH-CONC-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1117

IAP, AD

PCR 1028 R/B/W/T HIRL CL

RWY 18L: PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR

RWY 36R: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 70'. RVR-TMR

RWY 18R-36L: H12004X200 (ASPH-CONC-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1117

PCR 1139 R/B/W/T HIRL CL

RWY 18R: MALSR. TDZL. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR

RWY 36L: REIL. PAPI(P4L)—GA 3.0° TCH 69'. RVR-TMR

RWY 17R-35L: H10000X150 (CONC-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1117 PCR 1139 R/B/W/T

HIRL CL

RWY 17R: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR

RWY 35L: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 72'. RVR-TMR

RWY 17L-35R: H9001X150 (CONC-GRVD) S-120, D-250, 2D-550, 2D/2D2-1117 PCR 1090 R/B/W/T HIRL CL

RWY 17L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 72'. RVR-TMR

RWY 35R: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 73'. RVR-TMR

RUNWAY DECLARED DISTANCE INFORMATION

RWY 17L:TORA-9001 TODA-9001 ASDA-9001 LDA-9001

RWY 17R:TORA-10000 TODA-10000 ASDA-10000 LDA-10000

RWY 18L:TORA-12005 TODA-12005 ASDA-12005 LDA-12005

RWY 18R:TORA-12004 TODA-12004 ASDA-12004 LDA-12004

RWY 35L:TORA-10000 TODA-10000 ASDA-10000 LDA-10000

RWY 35R:TORA-9001 TODA-9001 ASDA-9001 LDA-9001

RWY 36L:TORA-12004 TODA-12004 ASDA-11621 LDA-11621

RWY 36R:TORA-12005 TODA-12005 ASDA-11601 LDA-11601

SERVICE: S2 FUEL 100LL, JET A MILITARY—FUEL A, A+ (C407-851-8304.) (NC-100LL)

AIRPORT REMARKS: Attended continuously. Birds on and in/ovf arpt. Use caution in/ovf Twy A along west ramp. Rwy 18L-36R ctr 75' keel section of rwy conc full length, ctr 100' keel section of rwy conc first 1000', both ends. Rest of rwy width is asph. Rwy 18R-36L ctr 87' keel section of rwy conc full length, rest of rwy width is asph. Last 3000' of Rwy 18R is conc full width. Unless advised by ATIS, dep flts on initial ctc with GND CON, act on West ramp, Airside 1 and 3 (Gates 1-59) use GND CON 121.8. Act at Airside 2 and 4 (Gates 60 and higher), use GND CON 126.4. When ORL ILS Rwy 07 and MCO ILS Rwys 17 and 18R simultaneous ops are conducted, ATC radar rqrd. Bright lgts on road btn Rwy 17R-35L and Rwy 17L-35R may be mistaken for rwy lgts. Act with wingspan greater than 214' must adhere to specific rwy and taxi rts. Ctc afld ops at 407-825-2036 for details. Rwy status lgts are in opr. All aircraft determined to be FAA Design Group IV and above must perform judgmental oversteering instead of cockpit cntrln steering when taxiing. Twy J3 and Twy J4 rstd to wingspan of less than 118'. Twy A, south of Twy A3, rstd to wingspan of less than 118'. PPR rqrd for wingspan 118' or greater. 24 hr PPR for acct equipped with weather modification or geoengineering eqpt 407-825-2036. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Flight Notification Service (ADCUS) avbl.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

AIRPORT MANAGER: 407-825-2020

WEATHER DATA SOURCES: ASOS (407) 270-2241 LLWAS. TDWR.

COMMUNICATIONS: D-ATIS ARR 121.25 D-ATIS DEP 120.525 UNICOM 122.95

® **ORLANDO APP/DEP CON** 119.4 (181°-310° 5500' and blo) 119.4 (061°-180° 4500' and blo) 135.3 (311°-060° 5500' and blo) 120.15 (181°-359° abv 5500') 124.8 (000°-180° abv 5000')

TOWER 124.3 (Rwy 18L-36R; Rwy 18R-36L) 118.45 (Rwy 17L-35R; Rwy 17R-35L)

GND CON 121.8 (West) 126.4 (East) **CLNC DEL** 134.7

CPDLC (LOGON KUSA) **AR OPS** 41.5 148.8

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

RADIO AIDS TO NAVIGATION: NOTAM FILE ORL.

(VH) (H) **VORTACW** 112.2 ORL Chan 59 N28°32.56' W81°20.10' 169° 6.9 NM to fld. 102/0E.

TACAN AZIMUTH unusable:

066°-084°

246°-289° byd 17 NM blo 2,000'

246°-289° byd 28 NM blo 2,500'

VOR unusable:

075°-089° byd 40 NM blo 8,000'

075°-089° byd 53 NM

090°-100° byd 40 NM

235°-245° byd 40 NM

260°-296° byd 40 NM blo 2,000'

260°-296° byd 46 NM blo 5,000'

260°-296° byd 57 NM

300°-314° byd 40 NM blo 4,000'

300°-314° byd 55 NM blo 6,000'

300°-314° byd 66 NM

320°-330° byd 40 NM

340°-345° byd 40 NM

ILS/DME 110.95 I-ARK Chan 46(Y) Rwy 17L. Class IIIE.

ILS/DME 111.75 I-DIZ Chan 54(Y) Rwy 17R. Class IIE.

ILS/DME 111.9 I-TFE Chan 56 Rwy 18R. Class IA.

ILS/DME 110.5 I-DDO Chan 42 Rwy 35L. Class IIIE.

ILS/DME 111.15 I-CER Chan 48(Y) Rwy 35R. Class IIIE.

ILS/DME 111.9 I-MCO Chan 56 Rwy 36L.

ILS/DME 110.7 I-OJP Chan 44 Rwy 36R. Class IIIE.