

WAAS
CH **70614**
W18A

APP CRS
176°

Rwy Ldg
TDZE **2173**
Apt Elev **2189**

RNAV (GPS) RWY 18
WEST WOODWARD (WWR)

RNP APCH - GPS.

Baro-VNAV and VDP NA when using GAG altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Inop table does not apply. When local altimeter setting not received, use GAG altimeter setting and increase LPV DA to 2413 feet and LNAV/VNAV DA to 2478 feet; increase all MDAs 40 feet and Circling visibility Cat D ¼ SM.

ODALS

MISSED APPROACH: Climb to 5000 direct TISSY and hold.

AWOS-3 118.425	KANSAS CITY CENTER 126.95 379.2	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------

ELEV **2189** TDZE **2173**

176°

81

2500 x 60

6002 x 100

36

REIL Rwy 36 0

MIRL Rwy 6-24 and 18-36 0

5000 TISSY

DEANA 4 NM Holding Pattern

FANIE 2.2 NM to RW18

RUNSY 3800

356° 7000

176° 4000

3800

2900

1 NM to RW18

1 NM 1.2 NM 2.8 NM 6 NM

GP 3.00° TCH 40

CATEGORY	A	B	C	D
LPV DA		2373-1	200 (200-1)	
LNAV/VNAV DA		2438-1	265 (300-1)	
LNAV MDA		2520-1	347 (400-1)	
CIRCLING	2660-1 471 (500-1)	2840-1 651 (700-1)	2940-2¼ 751 (800-2¼)	2960-2½ 771 (800-2½)

WOODWARD, OKLAHOMA

Amtd 1 03SEP26

36°26'N-99°31'W

WEST WOODWARD (WWR)
RNAV (GPS) RWY 18